

## OML50 - LED ARRAY DU HE CORNER T 940

31069 9400

 [Bekijk op website](#)


| Algemene info                   |   |
|---------------------------------|---|
| <b>LOCATIE</b>                  | binnen  |
| <b>STOF EN WATERDICHTHEID</b>   | IP20  |
| <b>GEWICHT (KG)</b>             | 1.4   |
| <b>INFO</b>                     | CLUSTER DOWN: 2898lm/m<br>CLUSTER UP: 2015lm/m<br>INCL.LED POWER SUPPLY<br>CABLING 1 CIRCUIT                                      |
| Elektrische info                |   |
| <b>ELEKTRISCH</b>               | 220-240V / 0 50-60Hz  |
| <b>KLASSE</b>                   | I   |
| <b>VOEDING INBEGREPEN</b>       | YES   |
| <b>DIM TYPE</b>                 | niet dimbaar  |
| <b>ENERGIE KLASSE</b>           | D   |
| <b>CERTIFICATES</b>             | EPD, RCM  |
| Info lichtbron                  |   |
| <b>LIGHTSOURCE NAME</b>         | LED   |
| <b>LICHTBRON</b>                | DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm)<br>UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm) |
| <b>TM-30 WAARDEN</b>            | Rf: 90 / Rg: 101  |
| <b>SMDC</b>                     | SDCM3   |
| <b>RISK-GROEP</b>               | RG1   |
| <b>LM80</b>                     | L80 > 60000   |
| <b>LED TECHNIEK (LICHTBRON)</b> | DOWN: 3802lm // 22,2W // 171lm/W<br>UP: 2644lm // 16,4W // 162lm/W  |

Notes: