





SUPERNOVA FLAT 95 PRISMATIC 930

20637 9300 W

AVAILABLE IN

BLACK 20637 9300 B

WHITE 20637 9300 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.ADJUSTABLE LED POWER SUPPLY - 2 settings: 1- 1860mA 2- 1300mA
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 1860: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm Or @ 1300: LED cluster 54,2W / CRI>90 (R9: 68) / 3000K / 8273lm
TM-30 VALUES	Rf: 89 / Rg: 97 @ 1300: Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 1860: 11477lm // 79,4W // 144lm/W Or @ 1300: 8273lm // 54,2W // 153lm/W
LED TECHNICS (LUMINAIRE)	@ 1860: 8583lm // 91,3W // 94lm/W Or @ 1300: 6187lm // 62,3W // 99lm/W

Options

SUSPENSION SET 25 3m

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m

CENTRAL SUSPENSION SUPERNOVA FLAT

For detailed installation instructions, please consult the manual : [20637_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO

CABLE BASE R ANO

☐

203 99 55 B


CABLE BASE R B

☐

203 99 55 W

CABLE BASE R W

☐



203 99 56 ANO

CABLE BASE S ANO

☐

203 99 56 B

CABLE BASE S B


☐

203 99 56 W

CABLE BASE S W

☐

Coversets



204 00 62 ANO

COVERSET R 62 ANO

☐

204 00 62 B


COVERSET R 62 B

☐

204 00 62 W

COVERSET R 62 W

☐



204 00 90 ANO





COVERSET R 90 ANO

☐

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC 930

20637 9300 W


	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC 930

20637 9300 W


Suspension parts




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 SUSPENSION SET 25 3m

☐

328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

Electric connection parts



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: