



SUPERLOOP HC 400 SBL 930

20553 9300 FG



AVAILABLE IN

NOIR 20553 9300 B

FLEMISH BRONZE 20553 9300 FBR

FLEMISH GOLD 20553 9300 FG

BLANC 20553 9300 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.9
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL 4 SEGMENTS EXCL.LED POWER SUPPLY 24-DC INCL.8 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.4 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED FLEX FP 45W / CRI>90 / 3000K / 5445lm)
LED TECHNICS (LIGHT SOURCE)	21780 lm // 180 W // 121 lm/W
LED TECHNICS (LUMINAIRE)	9801lm // 207W // 47lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20553_XXX0_HAND.pdf](#)




FINISH YOUR SPECIFICATION

le cable d'alimentation

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

les alimentations led











of Fixtures

	web2print_power_supply_info_box	Min current Max current
	300 89 24 80 ED1 LED POWER SUPPLY 24V-DC / 80W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 75	1/4 ☐
	300 89 24 150 LED POWER SUPPLY 24V-DC / 150W Dimtype: non dimmable Cutout dimension (mm): 75	2/4 ☐
	300 89 24 480 LED POWER SUPPLY 24V-DC / 480W DIN Dimtype: non dimmable	1 ☐

DELTALIGHT

SUPERLOOP HC 400 SBL 930

20553 9300 FG


	<u>300 90 003 ED1</u> 24V-DC / 4A DIM1 UNIT	1/4 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 30	
	<u>300 90 003 ED5</u> 24V-DC / 4A DIM5 UNIT	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 30	
	<u>300 90 010</u> 24V-DC / 2 x 4A WIRELESS DIM UNIT	1/4 ☐
	Dimtype: WDL = dimmable sans fil	
	<u>21012 0111</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM1	1/4 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 75	
	<u>21012 0121</u> LED POWER SUPPLY 24V-DC / 120W IP67 DIM1	1/4 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 75	
	<u>21012 0145</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM5	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 75	
	<u>21012 0155</u> LED POWER SUPPLY 24V-DC / 120W IP67 DIM5	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 75	
	<u>21012 0181</u> LED POWER SUPPLY 24V-DC / 90W DIM1	1/4 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 70	
	<u>21012 0191</u> LED POWER SUPPLY 24V-DC / 120W DIM1	1/4 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 70	
	<u>21012 0225</u> LED POWER SUPPLY 24V-DC / 100W DIM5	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 70	





DELTALIGHT

SUPERLOOP HC 400 SBL 930

20553 9300 FG

Equipements de contrôle divers		# of Fixtures
 web2print_power_supply_info_box		Min current Max current

	300 90 24 ED2 LED DIMMODULE 24V / 3CH / 6A DIM2	2/4 ☐
Dimtype: DALI ou bouton poussoir		

les sets pour recouvrement plafond		
	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐
	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐
	204 62 62 ANO COVERSET S 62 ANO	☐

DELTALIGHT


SUPERLOOP HC 400 SBL 930

20553 9300 FG

204 62 62 B COVERSET S 62 B

☐

204 62 62 W COVERSET S 62 W

☐


204 80 80 ANO COVERSET S 80 ANO

☐

204 80 80 B COVERSET S 80 B

☐

204 80 80 W COVERSET S 80 W

☐

204 90 90 ANO COVERSET S 90 ANO

☐


204 90 90 B COVERSET S 90 B

☐

204 90 90 W COVERSET S 90 W

☐


les accessoires de suspension



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

les accessoires pour connexions électriques



328 10 03 CONNECTION TRIMLESS O.F.A.


☐

Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT

SUPERLOOP HC 400 SBL 930

20553 9300 FG



15225 0360 B CONNECTION ST B



Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W



Notes: