



HALOSCAN ON 2 MP 92714 DIM8



23149 9218 B-B

AVAILABLE IN

NOIR-NOIR 23149 9218 B-B

NOIR-COULEUR OR 23149 9218 B-GC

BLANC-BLANC 23149 9218 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1286lm // 13,3W // 96lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23149_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière



Ø72

23110 0040

HALOSCAN LINEAR SPREAD LENS

☐



Ø72

23110 0050 B

HALOSCAN HONEYCOMB B

☐



Ø82

23110 0060 B

HALOSCAN KAP MP B

☐

23110 0060 W

HALOSCAN KAP MP W

☐

Notes: