



OML50 - PRISMATIC LENS DU HO 984mm 940 DIM5

31633 9405 B

AVAILABLE IN
BLACK 31633 9405 B



[View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 23,3W / CRI>90 (R9: 50) / 4000K / 3637lm UP: LED cluster 18,1W / CRI>90 (R9: 50) / 4000K / 2731lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3637lm // 23,3W // 160lm/W UP: 2731lm // 18,1W // 151lm/W

Options

WIRELESS CONTROL DIM5

Notes: