



OML50 - PRISMATIC LENS DU HO 984mm 940 DIM5

31633 9405 B

BESCHIKBAAR IN
ZWART 31633 9405 B

 [Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.5
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 23,3W / CRI>90 (R9: 50) / 4000K / 3637lm UP: LED cluster 18,1W / CRI>90 (R9: 50) / 4000K / 2731lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3637lm // 23,3W // 160lm/W UP: 2731lm // 18,1W // 151lm/W

Opties

WIRELESS CONTROL DIM5

Notes: