





## OBLIX S 15 927

15112 9200 FBRX

AVAILABLE IN  
**FLEMISH BRONZE OUTDOOR** 15112 9200 FBRX  
**ANTHRACITE** 15112 9200 N



[View on website](#)



### General info

|                                             |                                |
|---------------------------------------------|--------------------------------|
| <b>LOCATION</b>                             | outdoor                        |
| <b>INSTALLATION</b>                         | Floor Surface mounted          |
| <b>INGRESS PROTECTION</b>                   | IP55                           |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK03                           |
| <b>WEIGHT (KG)</b>                          | 1.4                            |
| <b>ADJUSTABILITY</b>                        | non adjustable                 |
| <b>INFORMATION</b>                          | INCL.LED POWER SUPPLY 350mA-DC |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 120-240V / 50-60Hz |
| <b>CLASS</b>        | II                 |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | E                  |
| <b>CERTIFICATES</b> | CB, EAC, ENEC, RCM |

### Lightsource info

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                              |
| <b>LIGHTSOURCE</b>                 | LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                 |
| <b>SDCM</b>                        | SDCM1                                            |
| <b>RISKGROUP</b>                   | RG1                                              |
| <b>LM80</b>                        | L90B10 > 50000                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 753lm // 5,8W // 129lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 533lm // 6,7W // 80lm/W                          |


### Options

PIN 17  
 CBOX  
 IP68 CONNECTION KIT  
 IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [15112\\_XXXX\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



**216 12 00** CBOX

☐

Cutout dimension (mm): 142 x 142




**216 12 01** IP68 CONNECTION KIT

☐

**216 12 02** IP68 CONNECTOR 3P

☐

Pins and plates for bollards



**15222 0170** PIN 17

☐

Notes: