



EXCLUSIVELY AVAILABLE IN INDIA

COMPO S HP TW 96541

9 15721 9030 B


AVAILABLE IN

NOIR 9 15721 9030 B

CHROME 9 15721 9030 C

CHROME FONCÉ 9 15721 9030 DC

BLANC 9 15721 9030 W



0-30°/355°



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.18
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 7,4W / CRI>90 / 2700K-6500K / 760lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	760lm // 7,4W // 90lm/W
LED TECHNICS (LUMINAIRE)	509lm // 8,5W // 60lm/W

Requirements

LED POWER SUPPLY 200 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15721_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 5800 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA	1

kit de montage	
 15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
Cutout dimension (mm): 55	
15710 0010 W MOUNTING KIT COMPO S TRIM W	☐
 15710 0040 MOUNTING KIT COMPO S TRIMLESS	☐
Cutout dimension (mm): 55	

modifier les dispositifs de lumière	
15710 0100 B COMPO S HONEYCOMB SINGLE USE B	☐
15710 0110 COMPO S LINEAR SPREAD LENS	☐
Cutout dimension (mm): 26,5	

DELTALIGHT

COMPO S HP TW 96541

9 15721 9030 B

<u>15710 0120</u>	COMPO S SPREAD LENS	☐
--------------------------	---------------------	--------------------------

Cutout dimension (mm): 26,5

<u>15710 0130</u>	COMPO S SOFTENING LENS	☐
--------------------------	------------------------	--------------------------

Cutout dimension (mm): 26,5

<u>15710 0140</u>	COMPO S GLASS SBL	☐
--------------------------	-------------------	--------------------------

Cutout dimension (mm): 26,5

Notes: