



COMPO S HP TW 96541

9 15721 9030 B


AVAILABLE IN

BLACK 9 15721 9030 B

CHROMED 9 15721 9030 C

DARK CHROMED 9 15721 9030 DC

WHITE 9 15721 9030 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.18
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 7,4W / CRI>90 / 2700K-6500K / 760lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	760lm // 7,4W // 90lm/W
LED TECHNICS (LUMINAIRE)	509lm // 8,5W // 60lm/W

Requirements	
LED POWER SUPPLY 200 mA - DC	

Accessories	
COMPO S HONEYCOMB SINGLE USE B	
COMPO S LINEAR SPREAD LENS	
COMPO S SPREAD LENS	
COMPO S SOFTENING LENS	
COMPO S GLASS SBL	

For detailed installation instructions, please consult the manual : [9_15721_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 5800 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA

1

Mounting kits



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W



15710 0040 MOUNTING KIT COMPO S TRIMLESS

Cutout dimension (mm): 55

Light altering devices

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

15710 0110 COMPO S LINEAR SPREAD LENS

DELTALIGHT

COMPO S HP TW 96541

9 15721 9030 B

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS



Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS



Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL



Cutout dimension (mm): 26,5

Notes: