



MINIGRID 67 ON 245 92725 DIM8

REFERENCE

100006 9228 B-W



AVAILABLE IN

BLACK-BLACK 100006 9228 B-B

BLACK-WHITE 100006 9228 B-W

WHITE-BLACK 100006 9228 W-B

WHITE-WHITE 100006 9228 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	0° to 30° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-25° INCL.DIMMABLE LED POWER SUPPLY 450mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 7,7W / CRI>90 (R9: 60) / 2700K / 885lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	1770lm // 15,4W // 115lm/W
LED TECHNICS (LUMINAIRE)	1244lm // 17,7W // 70lm/W

For detailed installation instructions, please consult the manual : [100006_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

MINIGRID 67 ON 245 92725 DIM8

100006 9228 B-W