

OML50 - LED ARRAY DU HE CORNER T 940 DIM5

31069 9405

 [Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.4
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm) UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm)
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3802lm // 22,2W // 171lm/W UP: 2644lm // 16,4W // 162lm/W
Opties	
WIRELESS CONTROL DIM5	

Notes: