

OML50 - LED ARRAY DU HE CORNER X 930 DIM5

31070 9305

 [View on website](#)


| General info | |
|------------------------------------|---|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0 |
| INFORMATION | CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |
| Electrical info | |
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | D |
| CERTIFICATES | EPD, RCM |
| Lightsource info | |
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1824lm) UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 3000K / 1267lm) |
| TM-30 VALUES | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 3648lm // 22,2W // 164lm/W UP: 2534lm // 16,4W // 155lm/W |
| Options | |
| WIRELESS CONTROL DIM5 | |

Notes: