
DELTALIGHT




NOCTA SQ155 DOWN-UP VWFL 927

REFERENCE 30128 9200 B

AVAILABLE IN
ALU GREY 30128 9200 A
BLACK 30128 9200 B
FLEMISH BRONZE OUTDOOR 30128 9200 FBRX
ANTHRACITE 30128 9200 N
WHITE 30128 9200 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x LENS INCL.LED POWER SUPPLY 350 mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 702lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1404lm // 11,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	857lm // 13,3W // 64lm/W

For detailed installation instructions, please consult the manual : **30128_XXX0_HAND.pdf**

DELTALIGHT

NOCTA SQ155 DOWN-UP VWFL 927

30128 9200 B

Notes: