



## M20/M26H - OBIN 93024 MDL

30513 9320 B

AVAILABLE IN

**BLACK** 30513 9320 B

**BRUSHED ALU** 30513 9320 BRA

**BRUSHED ANTHRACITE** 30513 9320 BRAT



**BRUSHED BROWN BRONZE** 30513 9320 BRBB

**BRUSHED GOLD** 30513 9320 BRG

**BRUSHED OLD BRONZE** 30513 9320 BROB

**CREAM** 30513 9320 CR

**WHITE** 30513 9320 W



[View on website](#)



### General info

|                           |                                                |
|---------------------------|------------------------------------------------|
| <b>LOCATION</b>           | indoor                                         |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted |
| <b>INGRESS PROTECTION</b> | IP20                                           |
| <b>WEIGHT (KG)</b>        | 0.5                                            |
| <b>ADJUSTABILITY</b>      | 0° to 45° swiveling, 360° rotatable            |
| <b>INFORMATION</b>        | LENS FL-24°<br>EXCL.LED POWER SUPPLY 48V-DC    |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC                           |

### Lightsource info

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                |
| <b>LIGHTSOURCE</b>                 | LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                    |
| <b>SDCM</b>                        | SDCM1                                              |
| <b>RISKGROUP</b>                   | RG1                                                |
| <b>LM80</b>                        | L90B10 > 50000                                     |
| <b>BEAMANGLE</b>                   | 24°                                                |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1524lm // 11,6W // 131lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1272lm // 13,3W // 95lm/W                          |

### Requirements

SPY 90 TUBE

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 75

For detailed installation instructions, please consult the manual : [30513\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

14

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

14

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

14

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

7

Dimtype: non-dimmable

# DELTALIGHT

## M20/M26H - OBIN 93024 MDL

30513 9320 B




63 114 125

**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

14 ☐

**Dimtype: non-dimmable**




17 298 30

**21012 0230** LED POWER SUPPLY 48V-DC / 100W

7 ☐

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**



22 392 30


**21012 0240** LED POWER SUPPLY 48V-DC / 200W

14 ☐

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Light altering devices



13 Ø75

**19810 0110 B** HONEYCOMB 75 SINGLE USE B

☐

# DELTALIGHT

## M20/M26H - OBIN 93024 MDL

30513 9320 B

### Finish your product

|                                                                                  |                       |                 |                          |
|----------------------------------------------------------------------------------|-----------------------|-----------------|--------------------------|
|  | <b>19810 0170 B</b>   | SPY 90 TUBE B   | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 CR</b>  | SPY 90 TUBE CR  | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 DC</b>  | SPY 90 TUBE DC  | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 FBR</b> | SPY 90 TUBE FBR | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 FG</b>  | SPY 90 TUBE FG  | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 GC</b>  | SPY 90 TUBE GC  | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 PB</b>  | SPY 90 TUBE PB  | <input type="checkbox"/> |
|                                                                                  | <b>19810 0170 W</b>   | SPY 90 TUBE W   | <input type="checkbox"/> |

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H profile

### Available Colours

|                                                                                     |                   |                     |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------|---------------------|---------------------------------------------------------------------------------------|
|  | <b>23359 0000</b> | SLM26H - PROFILE    |  |
|  | <b>23359 0010</b> | SLM26H - PROFILE 1m |  |
|  | <b>23359 0020</b> | SLM26H - PROFILE 2m |  |

# DELTALIGHT

## M20/M26H - OBIN 93024 MDL

30513 9320 B



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: