





SUPERNOVA FLAT 65 PRISMATIC SMOOTH UP 930 DIM5

20634 9305 B

AVAILABLE IN
NOIR 20634 9305 B
BLANC 20634 9305 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique, Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.6
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 930mA

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm
RVALUES	Rf: 89 / Rg: 97
SDMC	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	5360lm // 37,4W // 144lm/W
LED TECHNICS (LUMINAIRE)	4092lm // 43W // 95lm/W


Options

SUSPENSION SET 25 DIM 3m
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT



For detailed installation instructions, please consult the manual : [20634_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐






les sets pour recouvrement plafond

	<u>204 00 62 ANO</u> COVERSET R 62 ANO	☐
	<u>204 00 62 B</u> COVERSET R 62 B	☐
	<u>204 00 62 W</u> COVERSET R 62 W	☐
	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 65 PRISMATIC SMOOTH UP 930 DIM5

20634 9305 B


	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐
les accessoires de suspension		
	<u>274 97 10 B</u> CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B	☐

DELTALIGHT


SUPERNOVA FLAT 65 PRISMATIC SMOOTH UP 930 DIM5

20634 9305 B

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 ED SUSPENSION SET 25 DIM 3m

☐

328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

les accessoires pour connexions électriques



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: