

## INLET TRIMLESS L113 930



13217 9300 B-W

AVAILABLE IN

**BLACK-WHITE** 13217 9300 B-W

**GOLD COLORED-WHITE** 13217 9300 GC-W

**WHITE-WHITE** 13217 9300 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Wall Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	rectangle - KIT
<b>RECESSED DEPTH (MM)</b>	50
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	EXCL.LED POWER SUPPLY 24V-DC

### Electrical info

<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	1 x LEDFLEX 16,9W / CRI>90 / 3000K / 2085lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	2085lm // 16,9W // 123lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	648lm // 19,4W // 33lm/W

### Requirements

MOUNTING KIT INLET TRIMLESS L113  
LED POWER SUPPLY 24V-DC (Remote)

For detailed installation instructions, please consult the manual : [13217\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## INLET TRIMLESS L113 930

13217 9300 B-W

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W

8

Dimtype: non-dimmable

Cutout dimension (mm): 75




**21012 0101** LED POWER SUPPLY 24V-DC / 60W IP67 DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 65




**21012 0111** LED POWER SUPPLY 24V-DC / 90W IP67 DIM1

4

Dimtype: 1-10V

Cutout dimension (mm): 75




**21012 0121** LED POWER SUPPLY 24V-DC / 120W IP67 DIM1

6

Dimtype: 1-10V

Cutout dimension (mm): 75




**21012 0135** LED POWER SUPPLY 24V-DC / 60W IP67 DIM5

3

Dimtype: DALI

Cutout dimension (mm): 65




**21012 0145** LED POWER SUPPLY 24V-DC / 90W IP67 DIM5

4

Dimtype: DALI

Cutout dimension (mm): 75




**21012 0155** LED POWER SUPPLY 24V-DC / 120W IP67 DIM5

6

Dimtype: DALI

Cutout dimension (mm): 75



**21012 0160** LED POWER SUPPLY 24V-DC / 24W

1


Dimtype: non-dimmable

Cutout dimension (mm): 55

# DELTALIGHT

## INLET TRIMLESS L113 930

13217 9300 B-W




**21012 0171** LED POWER SUPPLY 24V-DC / 60W DIM1

3

**Dimtype: 1-10V**

**Cutout dimension (mm): 61**




**21012 0181** LED POWER SUPPLY 24V-DC / 90W DIM1

4

**Dimtype: 1-10V**

**Cutout dimension (mm): 70**




**21012 0191** LED POWER SUPPLY 24V-DC / 120W DIM1

6

**Dimtype: 1-10V**

**Cutout dimension (mm): 70**




**21012 0205** LED POWER SUPPLY 24V-DC / 60W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 61**




**21012 0225** LED POWER SUPPLY 24V-DC / 100W DIM5

5

**Dimtype: DALI**

**Cutout dimension (mm): 70**

### Mounting kits



**13210 0070** MOUNTING KIT INLET TRIMLESS L113

**Cutout dimension (mm): 1145 x 75**

Notes: