DELTALIGHT



OML50 - LED ARRAY DU HE 1640mm 940

REFERENCE 31042 9400

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
INFORMATION	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 27,8W / CRI>90 (R9: 50) / 4000K / 4752lm UP: LED cluster 20,4W / CRI>90 (R9: 50) / 4000K / 3304lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 4752lm // 27,8W // 171lm/W UP: 3304lm // 20,4W // 162lm/W

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 08/10/2026