





SOLI - 66 NLT 952745 Q-DIM

REFERENCE 27126 723Q W

AVAILABLE IN
BLACK 27126 723Q B
WHITE 27126 723Q W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC NLT = Natural Light Technology Optional REFLECTORS 18° & 30° available
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21,1W / CRI>95 (R9: 96) / 2700K / 1925lm
TM-30 VALUES	Rf: 97 / Rg: 102
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1925lm // 21,1W // 91lm/W
LED TECHNICS (LUMINAIRE)	1321lm // 24,3W // 54lm/W

Requirements	
SPY 66 TUBE	
LED POWER SUPPLY 48V-DC	






Accessories	
HONEYCOMB 57	
SPREAD LENS 57	
LINEAR SPREAD LENS 57	
SOFTENING LENS 57	
GLASS SBL 57	

SOLI - 66 NLT 952745 Q-DIM

27126 723Q W

For detailed installation instructions, please consult the manual : [27126_XXXQ_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
<div><div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		Min current Max current
<div><div></div><div>300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable</div></div>	4	☐
<div><div></div><div>300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable</div></div>	9	☐
<div><div></div><div>21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40</div></div>	4	☐
<div><div></div><div>21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40</div></div>	8	☐
Light altering devices		
<div><div></div><div>24611 0150 B HONEYCOMB 57 SINGLE USE B</div></div>		☐
<div><div></div><div>24611 0160 GLASS SBL 57</div></div>		☐


DELTALIGHT

SOLI - 66 NLT 952745 Q-DIM


27126 723Q W




24611 0170 LINEAR SPREAD LENS 57

☐

24611 0190 SOFTENING LENS 57

☐


24611 0200 SPREAD LENS 57

☐

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

DELTALIGHT

SOLI - 66 NLT 952745 Q-DIM

27126 723Q W





24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°



COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
<div> </div> <p>27111 0020 SOLI - PROFILE 2m</p>	<div></div>
<div> </div> <p>27111 0030 SOLI - PROFILE 3m</p>	<div></div>

Notes: