



OML50 - LED ARRAY DU HE 1640mm 940 DIM5

31042 9405



[View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
INFORMATION	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 27,8W / CRI>90 (R9: 50) / 4000K / 4752lm UP: LED cluster 20,4W / CRI>90 (R9: 50) / 4000K / 3304lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 4752lm // 27,8W // 171lm/W UP: 3304lm // 20,4W // 162lm/W

Options

WIRELESS CONTROL DIM5

Notes: