

## OML50 - LED ARRAY DU HE 1640mm 940 DIM5

31042 9405



[Bekijk op website](#)



### Algemene info

|                               |  |
|-------------------------------|--|
| <b>LOCATIE</b>                | binnen   |
| <b>STOF EN WATERDICHTHEID</b> | IP20   |
| <b>GEWICHT (KG)</b>           | 1.8  |
| <b>INFO</b>                   | CLUSTER DOWN: 2898lm/m<br>CLUSTER UP: 2015lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |

### Elektrische info

|                           |                      |
|---------------------------|----------------------|
| <b>ELEKTRISCH</b>         | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>             | I                    |
| <b>VOEDING INBEGREPEN</b> | YES                  |
| <b>DIM TYPE</b>           | DALI                 |
| <b>ENERGIE KLASSE</b>     | D                    |
| <b>CERTIFICATES</b>       | EPD, RCM             |

### Info lichtbron

|                                 |  |
|---------------------------------|--|
| <b>LIGHTSOURCE NAME</b>         | LED  |
| <b>LICHTBRON</b>                | DOWN: LED cluster 27,8W / CRI>90 (R9: 50) / 4000K / 4752lm<br>UP: LED cluster 20,4W / CRI>90 (R9: 50) / 4000K / 3304lm |
| <b>TM-30 WAARDEN</b>            | Rf: 90 / Rg: 101   |
| <b>SMDC</b>                     | SDCM3  |
| <b>RISK-GROEP</b>               | RG1  |
| <b>LM80</b>                     | L80 > 60000  |
| <b>LED TECHNIEK (LICHTBRON)</b> | DOWN: 4752lm // 27,8W // 171lm/W<br>UP: 3304lm // 20,4W // 162lm/W   |

### Opties

WIRELESS CONTROL DIM5

Notes: