





MULTINOVA 55 OK 800 930 DIM4

28025 9304 W

AVAILABLE IN
NOIR 28025 9304 B
COULEUR OR 28025 9304 GC
BLANC 28025 9304 W



[View on website](#)






General info	
LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	8.5
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	INCL.PC SBL ADJUSTABLE 0-90°/355° INCL.DIMMABLE LED POWER SUPPLY
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI ou DSI ou bouton poussoir
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm
RVALUES	Rf: 89 / Rg: 97
SDMC	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4767lm // 34,4W // 139lm/W
LED TECHNICS (LUMINAIRE)	3842lm // 39,6W // 97lm/W
Options	
COVERSET R 62-90-100	

For detailed installation instructions, please consult the manual : [28025_XXX4_HAND.pdf](#)

FINISH YOUR SPECIFICATION

les sets pour recouvrement plafond

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐
	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

Notes: