

OML50 - LED ARRAY DU HE CORNER X 940 DIM5

31070 9405



Bekijk op website



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm) UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm)
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3802lm // 22,2W // 171lm/W UP: 2644lm // 16,4W // 162lm/W

Opties

WIRELESS CONTROL DIM5

Notes: