

OML50 - LED ARRAY DU HE CORNER X 940 DIM5

31070 9405



Bekijk op website



Algemene info

| | |
|-------------------------------|---|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 0 |
| INFO | CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |

Elektrische info

| | |
|---------------------------|----------------------|
| ELEKTRISCH | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING INBEGREPEN | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATES | EPD, RCM |

Info lichtbron

| | |
|---------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LICHTBRON | DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm) UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm) |
| TM-30 WAARDEN | Rf: 90 / Rg: 101 |
| SMDC | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | DOWN: 3802lm // 22,2W // 171lm/W UP: 2644lm // 16,4W // 162lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: