DELTALIGHT

OML50 - LED ARRAY DU TW CORNER L 950 DIM5

REFERENCE 31071 9005

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: 2 x (LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm) UP @ 2700K: 2 x (LED cluster 7,4W / CRI>90 (R9: 50) / 2700K-5000K / 976lm) Or DOWN @ 5000K: 2 x (LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm) UP @ 5000K: 2 x (LED cluster 6,8W / CRI>90 (R9: 50) / 2700K-5000K / 1168lm)
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 3904lm // 29,8W // 131lm/W UP @ 2700K: 1952lm // 14,8W // 131lm/W Or DOWN @ 5000K: 4672lm // 27W // 173lm/W UP @ 5000K: 2336lm // 13,6W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes: