



OML50 - LED ARRAY DU HE 1968mm 930

31043 9300



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.1
INFO	CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 33,4W / CRI>90 (R9: 50) / 3000K / 5472lm UP: LED cluster 24,5W / CRI>90 (R9: 50) / 3000K / 3802lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 5472lm // 33,4W // 164lm/W UP: 3802lm // 24,5W // 155lm/W

Notes: