



COMPO S HP 93020

9 15719 9320 B



AVAILABLE IN

NOIR 9 15719 9320 B

CHROME 9 15719 9320 C

CHROME FONCÉ 9 15719 9320 DC

BLANC 9 15719 9320 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.166
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9,3W / CRI>90 / 3000K / 920lm
SDMC	SDCM2
RISKGROUP	RG1
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	920lm // 9,3W // 100lm/W
LED TECHNICS (LUMINAIRE)	730lm // 10,7W // 68lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15719_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 3100 LED POWER SUPPLY 18W NO DIM 1400mA	1->4 ☐
15710 3400 LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA	1->2 ☐
15710 3900 LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA	1 ☐
15710 4600 LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA	1 ☐
15710 5000 LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13 ☐
Dimtype: DALI	
15710 5400 LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1->2 ☐
Dimtype: DALI	

kit de montage

	15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
	Cutout dimension (mm): 55	
	15710 0010 W MOUNTING KIT COMPO S TRIM W	☐

COMPO S HP 93020

9 15719 9320 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

modifier les dispositifs de lumière

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: