



# INLET



Our Inlet is a very popular wall recessed fixture for guidance light in hallways and staircases. A narrow beam of light produces a triangular shaped light effect on the floor. Available with trim or mounted flush in the wall, perfect for usage in residential applications.

Specification	
Wall Cut-out:	7/8" x 6 11/16"
Adjustability:	Fixed
Rating:	IP20

Performance	
LED Maintenance:	L90>36,000h
McAdam Step:	3
CRI:	80
*SP:	1.1W

Delivered Lumens	2700K	3000K
Inlet:	16Lm	16Lm

**Listing**

ETL certified to US and Canadian safety standards.

**Warranty**

5-year limited warranty.

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: ILT-SP30FIO-W-FLRMTD8-120

Luminaire	Power	CCT	Function	Style	Finish	Installation	Application	Controls***
ILT INLET	SP Standard Power	27 2700K  30 3000K	FI Fixed, Interior Use	O Open	A Alu Grey  W White	CB Enclosed box for concrete  FL Flush kit for mud into drywall  PK Plate for stucco, concrete, or brick with plaster (any thickness)  NA No optional accessory	RMT Remote Power Supply	D1-UNV 0-10V dim 120-277V  D8-120 FE ELV dim 120V

\*\*\* Contact factory for additional dimming options.



## Related Products

Heli, Heli X (exterior), Mini Logic, Logic W



## Finish Options


### INLET



LIGHT EFFECT  
(VIEW FROM ABOVE)

## Photometric Data

### INLET




## Installation Options

### REMOTE DRIVER

(With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2  
A: 203mm x B: 64mm x C: 64mm

- For Remote application
- ETL Listed
- Damp rated




### REMOTE DRIVER


(With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4  
A: 203mm x B: 72mm x C: 108mm


- For Remote application
- ETL Listed
- Damp rated



### CB - CONCRETE BOX 145



### FL - FLUSH MOUNTING KIT



### PK - PLASTER KIT 145





## Driver Options

### D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

### Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

### D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

### Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.