




INFORM SQ F282-6 94067

25527 9420 W-W

AVAILABLE IN
BLACK-BLACK 25527 9420 B-B
BLACK-FLEMISH GOLD 25527 9420 B-FG
WHITE-BLACK 25527 9420 W-B
WHITE-WHITE 25527 9420 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	non adjustable
INFORMATION	72 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 600/900mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 7-11,2W / CRI>90 (R9: 50) / 4000K / 1114-1610lm)
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	4830lm // 33,6W // 144lm/W
LED TECHNICS (LUMINAIRE)	4217lm // 38,6W // 109lm/W
Requirements	
INFORM POWER SUPPLY 45W	

For detailed installation instructions, please consult the manual : [25527_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
360 121 30	25510 0070 INFORM POWER SUPPLY 50W	1
70 215 131	25510 0385 INFORM POWER SUPPLY 45W DIM5	1
70 215 131	25510 0430 INFORM POWER SUPPLY 45W	1

Notes: