



LOGIC LINEAR ON 440 93015 DIM5

30827 9315 B

AVAILABLE IN



ALU GREY 30827 9315 A

BLACK 30827 9315 B

FLEMISH BRONZE OUTDOOR 30827 9315 FBRX

ANTHRACITE 30827 9315 N

WHITE 30827 9315 W



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
INFORMATION	8 x LENS SP-15° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 60) / 3000K / 1798lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	1798lm // 14,4W // 121lm/W
LED TECHNICS (LUMINAIRE)	1575lm // 16,6W // 95lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC


Options


THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30827_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current

	21032 0390 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	5
--	---	------------------------

Fixation components		
	30810 0040 LOGIC LINEAR 880 BOX EXTEND	
	30810 0040 INOX WALL BRACKET SET 60 INOX	
	30810 0040 N WALL BRACKET SET 60 N	
	30810 0050 INOX WALL BRACKET SET 100 INOX	
	30810 0050 N WALL BRACKET SET 100 N	
	30810 0060 INOX WALL BRACKET SET 200 INOX	
	30810 0060 N WALL BRACKET SET 200 N	

DELTALIGHT

LOGIC LINEAR ON 440 93015 DIM5

30827 9315 B



30810 0070 INOX FLOOR BRACKET SET INOX

☐

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0100 THROUGH WIRING SET IP68 440

☐

Notes: