



INFORM SQ F282-10 92767

25528 9220 B-B



AVAILABLE IN

BLACK-BLACK 25528 9220 B-B

BLACK-FLEMISH GOLD 25528 9220 B-FG

WHITE-BLACK 25528 9220 W-B

WHITE-WHITE 25528 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	120 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 1000/1500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 35,2-55,8W / CRI>90 (R9: 50) / 2700K / 5064-7320lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	7320lm // 55,8W // 131lm/W
LED TECHNICS (LUMINAIRE)	6390lm // 64,2W // 100lm/W

Requirements

INFORM POWER SUPPLY 60W

For detailed installation instructions, please consult the manual : [25528_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
360 21 30	25510 0080 INFORM POWER SUPPLY 75W	1
85 220 131	25510 0405 INFORM POWER SUPPLY 60W DIM5	1
85 220 131	25510 0450 INFORM POWER SUPPLY 60W	1

Notes: