





## TWEETER M ON 1 93033 DIM8

418 51 811 932 ED8 B-C

AVAILABLE IN

**BLACK-CHROMED** 418 51 811 932 ED8 B-C

**WHITE-WHITE** 418 51 811 932 ED8 W-W



[View on website](#)



| General info                |                                                             |
|-----------------------------|-------------------------------------------------------------|
| LOCATION                    | indoor                                                      |
| INSTALLATION                | Ceiling Surface mounted, Wall Surface mounted               |
| INGRESS PROTECTION          | IP20                                                        |
| WEIGHT (KG)                 | 0.8                                                         |
| ADJUSTABILITY               | 0° to 45° swiveling, 355° rotatable                         |
| INFORMATION                 | REFLECTOR FL-33°<br>INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |
| Electrical info             |                                                             |
| ELECTRICAL                  | 220-240V / 50-60Hz                                          |
| CLASS                       | II                                                          |
| POWER SUPPLY                | YES                                                         |
| DIM TYPE                    | mains (phase cut-off)                                       |
| ENERGY CLASS                | D                                                           |
| CERTIFICATES                | CB, ENEC, RCM                                               |
| Lightsource info            |                                                             |
| LIGHTSOURCE NAME            | LED                                                         |
| LIGHTSOURCE                 | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm           |
| TM-30 VALUES                | Rf: 90 / Rg: 99                                             |
| SDCM                        | SDCM1                                                       |
| RISKGROUP                   | RG1                                                         |
| LM80                        | L90B10 > 50000                                              |
| BEAMANGLE                   | 33°                                                         |
| LED TECHNICS (LIGHT SOURCE) | 1089lm // 8,6W // 127lm/W                                   |
| LED TECHNICS (LUMINAIRE)    | 867lm // 9,9W // 88lm/W                                     |


For detailed installation instructions, please consult the manual : [418\\_51\\_811\\_XXX\\_HAND.pdf](#)

TWEETER M ON 1 93033 DIM8

418 51 811 932 ED8 B-C

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: