
DELTALIGHT




# M26L - BOXY L A TW 96545 DIM5

**REFERENCE** 10743 9035 B-B

AVAILABLE IN
**BLACK-BLACK** 10743 9035 B-B
**BLACK-FLEMISH BRONZE** 10743 9035 B-FBR
**BLACK-FLEMISH GOLD** 10743 9035 B-FG
**WHITE-WHITE** 10743 9035 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | REFLECTOR WFL-45°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 45° |
| **LED TECHNICS (LIGHT SOURCE)** | 1087lm // 9W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 843lm // 10,4W // 81lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

LED POWER SUPPLY 48V-DC

**Accessories**

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

DELTALIGHT

# M26L - BOXY L A TW 96545 DIM5

10743 9035 B-B

For detailed installation instructions, please consult the manual : **10743_XXX5_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 9

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 23


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 9

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 19

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**

### Light altering devices




**251 70 03 01 B** BOXY HONEYCOMB B

**251 70 03 01 W** BOXY HONEYCOMB W





**251 70 03 04 B** BOXY SOFTENING LENS B

DELTALIGHT

# M26L - BOXY L A TW 96545 DIM5

10743 9035 B-B





**251 70 03 04 W** BOXY SOFTENING LENS W




**251 70 03 05 B** BOXY GLASS SBL B

**251 70 03 05 W** BOXY GLASS SBL W

## COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) | Available Colours |
|---|---|
|  **23358 0000** SLM26L - PROFILE | |
|  **23358 0010** SLM26L - PROFILE 1m | |
|  **23358 0020** SLM26L - PROFILE 2m | |
|  **23358 0030** SLM26L - PROFILE 3m | |



Notes: