

OML50 - LED ARRAY DU HE 1312mm EM-3H 940 DIM5

31222 9405



 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
INFORMATION	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,3W / CRI>90 (R9: 50) / 4000K / 3802lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3802lm // 22,3W // 171lm/W UP: 2643lm // 16,3W // 162lm/W

Options

WIRELESS CONTROL DIM5

Notes: