

OML50 - LED ARRAY DU HE 1312mm EM-3H 940 DIM5

31222 9405



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.7
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 22,3W / CRI>90 (R9: 50) / 4000K / 3802lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3802lm // 22,3W // 171lm/W UP: 2643lm // 16,3W // 162lm/W

Opties

WIRELESS CONTROL DIM5

Notes: