



NIME II WALLWASH 930

26416 9300 B

AVAILABLE IN
BLACK 26416 9300 B
WHITE 26416 9300 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 67
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	9,5-12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350-700mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2-4,3W / CRI>90 (R9: 50) / 3000K / 228-404lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	404lm // 4,3W // 94lm/W
LED TECHNICS (LUMINAIRE)	354lm // 4,9W // 72lm/W
Requirements	
LED POWER SUPPLY 350 / 500 / 700mA-DC DIM	

For detailed installation instructions, please consult the manual : [26416_XXX0_HAND.pdf](#)






NIME II WALLWASH 930

26416 9300 B

CEILING COMPATIBILITY











Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	12(12) 12(11) 11(9) ☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	8(7) 8(5) 7(3) ☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	4->19(19) 18(13) 13(9) ☐
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non-dimmable Cutout dimension (mm): 40	7(4) ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	3->8(7) 6(5) 4(3) ☐










NIME II WALLWASH 930

26416 9300 B

	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2->8(7) 6(5) 4(3)	☐
Dimtype: DALI			
Cutout dimension (mm): 55			
	21012 0010 LED POWER SUPPLY MULTI POWER	3->7 2->7 2->7	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 50			
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	2->9 2->9 2->8	☐
Dimtype: 1-10V			
Cutout dimension (mm): 54			
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	2->9 2->9 2->8	☐
Dimtype: DALI			
Cutout dimension (mm): 54			
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	2->9 2->9 2->8	☐
Dimtype: WDL = wireless dimmable			
Cutout dimension (mm): 54			
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	3->4	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 50			
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	5->7	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 50			
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	3->4 3->4	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 55			
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	6->8 6->8	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 55			
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2->7 2->6 2->4	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 48			

NIME II WALLWASH 930

26416 9300 B

	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	3->3	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 40		
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	3->3	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 40		
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8	3->3	☐
	Dimtype: mains (phase cut-off)		
	Cutout dimension (mm): 40		
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	8(7)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	6(3)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	8(5)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	7	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	7	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	6	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		

DELTALIGHT

NIME II WALLWASH 930

26416 9300 B

Notes: