



## LOGIC LINEAR ON 440 93015 DIM5

30827 9315 FBRX

AVAILABLE IN



**ALU GREY** 30827 9315 A

**BLACK** 30827 9315 B

**FLEMISH BRONZE OUTDOOR** 30827 9315 FBRX

**ANTHRACITE** 30827 9315 N

**WHITE** 30827 9315 W



[View on website](#)



| General info                         |                                                                     |
|--------------------------------------|---------------------------------------------------------------------|
| LOCATION                             | outdoor                                                             |
| INSTALLATION                         | Floor Surface mounted, Wall Surface mounted                         |
| INGRESS PROTECTION                   | IP67                                                                |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07                                                                |
| WEIGHT (KG)                          | 1                                                                   |
| INFORMATION                          | 8 x LENS SP-15°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |
| Electrical info                      |                                                                     |
| ELECTRICAL                           | 48V-DC                                                              |
| CLASS                                | III                                                                 |
| DIM TYPE                             | DALI                                                                |
| ENERGY CLASS                         | E                                                                   |
| CERTIFICATES                         | CB, ENEC                                                            |
| Lightsource info                     |                                                                     |
| LIGHTSOURCE NAME                     | LED                                                                 |
| LIGHTSOURCE                          | LED cluster 14,4W / CRI>90 (R9: 60) / 3000K / 1798lm                |
| TM-30 VALUES                         | Rf: 92 / Rg: 99                                                     |
| SDCM                                 | SDCM3                                                               |
| RISKGROUP                            | RG2                                                                 |
| LM80                                 | L80 > 150000                                                        |
| BEAMANGLE                            | 15°                                                                 |
| LED TECHNICS (LIGHT SOURCE)          | 1798lm // 14,4W // 121lm/W                                          |
| LED TECHNICS (LUMINAIRE)             | 1575lm // 16,6W // 95lm/W                                           |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC


### Options


THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30827\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                          |  | # of Fixtures             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------|
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |  | Min current   Max current |

|                                                                                  |                                                                                                               |                        |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|------------------------|
|  | <b>21032 0390</b> LED POWER SUPPLY 48V-DC / 90W<br><br>Dimtype: non-dimmable<br><br>Cutout dimension (mm): 75 | 5 <input type="text"/> |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|------------------------|

| Fixation components                                                                |                                                  |                      |
|------------------------------------------------------------------------------------|--------------------------------------------------|----------------------|
|  | <b>30810 0040</b> LOGIC LINEAR 880 BOX EXTEND    | <input type="text"/> |
|                                                                                    | <b>30810 0040 INOX</b> WALL BRACKET SET 60 INOX  | <input type="text"/> |
|                                                                                    | <b>30810 0040 N</b> WALL BRACKET SET 60 N        | <input type="text"/> |
|  | <b>30810 0050 INOX</b> WALL BRACKET SET 100 INOX | <input type="text"/> |
|                                                                                    | <b>30810 0050 N</b> WALL BRACKET SET 100 N       | <input type="text"/> |
|  | <b>30810 0060 INOX</b> WALL BRACKET SET 200 INOX | <input type="text"/> |
|                                                                                    | <b>30810 0060 N</b> WALL BRACKET SET 200 N       | <input type="text"/> |

# DELTALIGHT

## LOGIC LINEAR ON 440 93015 DIM5

30827 9315 FBRX



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0100** THROUGH WIRING SET IP68 440

☐

Notes: