
DELTALIGHT




M20/M26H - SPY FOCUS LP 930 DIM5

REFERENCE 23379 9305 W

AVAILABLE IN
BLACK 23379 9305 B
FLEMISH BRONZE 23379 9305 FBR
FLEMISH GOLD 23379 9305 FG
WHITE 23379 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	ADJUSTABLE BEAM 8°-43° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	8°-43°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	417lm // 9,9W // 42lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **23379_XXXX_HAND.pdf**

M20/M26H - SPY FOCUS LP 930 DIM5

23379 9305 W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 8


Dimtype: non-dimmable

Cutout dimension (mm): 75




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 9

Dimtype: non-dimmable




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 14

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 23


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 9

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 19

Dimtype: non-dimmable

Cutout dimension (mm): 40

Power box


of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

M20/M26H - SPY FOCUS LP 930 DIM5


23379 9305 W



23380 0010 B SLM26H - POWERBOX 48V-DC / 96W B — 10

Dimtype: non-dimmable

23380 0010 W SLM26H - POWERBOX 48V-DC / 96W W — 10







23380 0020 B SLM26H - MID POWERBOX 48V-DC / 96W B — 10

Dimtype: non-dimmable

23380 0020 W SLM26H - MID POWERBOX 48V-DC / 96W W — 10

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL	Available Colours
 **30411 9205** SHIFTLINE M26H + SBL 2m DIM5	
 **30411 9305** SHIFTLINE M26H + SBL 2m DIM5	
 **30412 9205** SHIFTLINE M26H + SBL 3m DIM5	
 **30412 9305** SHIFTLINE M26H + SBL 3m DIM5	
 **30413 9205** SHIFTLINE M26H + SBL 4m DIM5	
 **30413 9305** SHIFTLINE M26H + SBL 4m DIM5	


DELTALIGHT

M20/M26H - SPY FOCUS LP 930 DIM5


23379 9305 W

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE




23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m

SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m




420 20 20 00 SPM20 - PROFILE 2m


DELTALIGHT

M20/M26H - SPY FOCUS LP 930 DIM5

23379 9305 W



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B

Notes: