DELTALIGHT



NIME II WALLWASH 930

REFERENCE 26416 9300 W

AVAILABLE IN
BLACK 26416 9300 B
WHITE 26416 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 67
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	9,5-12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350-700mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2-4,3W / CRI>90 (R9: 50) / 3000K / 228-404lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	404lm // 4,3W // 94lm/W
LED TECHNICS (LUMINAIRE)	354lm // 5W // 72lm/W

Requirements

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

For detailed installation instructions, please consult the manual : **26416_XXX0_HAND.pdf**

DELTALIGHT

NIME II WALLWASH 930

26416 9300 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 12(12) | 12(11) | 11(9) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 8(7) | 8(5) | 7(3) ☐

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 4->19(19) | 18(13) | 13(9) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 7(4) ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 3->8(7) | 6(5) | 4(3) ☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 55

NIME II WALLWASH 930

26416 9300 W



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 2->8(7) | 6(5) | 4(3)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0010 LED POWER SUPPLY MULTI POWER — 3->7 | 2->7 | 2->7

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 2->9 | 2->9 | 2->8

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 2->9 | 2->9 | 2->8

Dimtype: DALI

Cutout dimension (mm): 54



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 2->9 | 2->9 | 2->8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 5->7

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 3->4 | 3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 6->8 | 6->8

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2->7 | 2->6 | 2->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48

NIME II WALLWASH 930

26416 9300 W



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 — 3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 — 3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 — 3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 8(7)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 — 6(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 8(5)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 7

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 7

Dimtype: DALI

Cutout dimension (mm): 30



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 6

Dimtype: DALI

Cutout dimension (mm): 30

NIME II WALLWASH 930

26416 9300 W

Notes: