





B-LINER 6522 IP

REFERENCE 388 01 22 W

AVAILABLE IN
ALU GREY 388 01 22 A
ANTHRACITE 388 01 22 N
WHITE 388 01 22 W



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY INCL.1 x PC SBL
Electrical info	
ELECTRICAL	110-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,7W / CRI>90 (R9: 50) / 3000K / 2159lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2159lm // 14,7W // 147lm/W
LED TECHNICS (LUMINAIRE)	1799lm // 16,9W // 106lm/W

For detailed installation instructions, please consult the manual : [388_01_22_HAND.pdf](#)

Notes:

DELTALIGHT

B-LINER 6522 IP

388 01 22 W