ONE-AND-ONLY P



It not only perfectly embraces the light source, it reinforces it in multiple aspects. Allowing you to have up to 5 lines of light out of 1 profile, 3 for direct and 2 for indirect lighting. The soft glow of the light along the sides of the profile makes the One-And-Only float through the air, a powerful blend of light for an eye-catching look.

Specification	
Installation Method:	4" junction box
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI:	90
SDCM:	3
LED Maintenance:	L70>40,000h

*Power	Down	Up
Standard Power Length 12:	39.8W	26.6W
Standard Power Length 19:	64.5W	43W

Delivered Lumens	3000K (Down/Up)	3500K (Down/Up)
One-And-Only L12:	2176 / 1309	2176 / 1309
One-And-Only L19:	5118 / 2779	5118 / 2779

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: OAOL12-SPDU35-GC-B-PCPRB-INCD1-UNV

Luminaire	Shape	Length	Downlight*	Uplight*	CCT	Finish	Style	Installation	Hardware Finish[1]	Application	Controls***
OAO ONE-AND-ONLY	**L** Linear	**12** 1181mm 46 1/2" **19** 1902mm 74 7/8"	**SP** Standard Power	**DU** Downlight with uplight	**30** 3000K **35** 3500K	**B-B** Black-Black **GC-B** Gold Colored-Black **W-W** White-White	**PC** Pendant, 5' cables, 2 suspension points	**PR** Round coverplate for 4" junction box **PS** Square coverplate for 4" junction box	**B** Black **W** White	**INC** Integral Power Supply	**D1-UNV** 0-10V dim 120-277V


1 Applies to PS & PR (coverplate).
*** Contact factory for additional dimming options.

Related Products


One-And-Only Profile (made-to-measure lengths)

Finish Options

ONE-AND-ONLY L12



ONE-AND-ONLY L19



FINISH



BLACK-BLACK


GOLD COLORED-BLACK


WHITE-WHITE


Photometric Data

ONE-AND-ONLY




Installation Options

PR - COVERPLATE R 104



BLACK or WHITE
Requires 4" junction box

PR - COVERPLATE S 103



BLACK or WHITE
Requires 4" junction box

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.97
- Efficiency @ Full Load ≥89
- THD @ Full Load <10%

Dimmer Compatibility

- Levition IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

DELTALIGHT