

ONE-AND-ONLY P



It not only perfectly embraces the light source, it reinforces it in multiple aspects. Allowing you to have up to 5 lines of light out of 1 profile, 3 for direct and 2 for indirect lighting. The soft glow of the light along the sides of the profile makes the One-And-Only float through the air, a powerful blend of light for an eye-catching look.

Specification	
Installation Method:	4" J-Box
Cable Length Suspension:	5'
Adjustability:	Fixed
Rating:	IP20

Performance	
LED Maintenance:	L70>40,000h
McAdam Step:	3
CRI:	90

*Power	Down	Up
One-And-Only L12 SP:	34.6W	23.1W
One-And-Only L19 SP:	56.1W	37.4W

Delivered Lumens	3000K	3500K
One-And-Only L12:	3485Lm	3485Lm
One-And-Only L19:	5643Lm	5643Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: OAOL12-SPDU35-GC-B-PCPRB-INCD1-UNV

Luminaire	Shape	Length	Downlight*	Uplight*	CCT	Finish	Style	Installation	Hardware Finish ⁽¹⁾	Application	Controls***
OAO ONE-AND-ONLY	Linear	12 1181mm 46 1/2"	SP Standard Power	DU Downlight with uplight	30 3000K	B-B Black-Black	PC Pendant, 2 suspension points	PR Round coverplate for 4" junction box	B Black W White	INC Integral Power Supply	D1-UNV 0-10V dim 120-277V
		19 1902mm 74 7/8"			35 3500K	GC-B Gold Colored- Black					
					W-W White-White	PS Square coverplate for 4" junction box					

¹Applies to PS & PR (coverplate).
*** Contact factory for additional dimming options.


Related Products

One-And-Only Profile




Finish Options

ONE-AND-ONLY L12



ONE-AND-ONLY L19




FINISH




Installation Options

PR - COVERPLATE R 104



BLACK or WHITE
Requires 4" junction box


PR - COVERPLATE S 103



BLACK or WHITE
Requires 4" junction box

Photometric Data

ONE-AND-ONLY



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.97
- Efficiency @ Full Load ≥89
- THD @ Full Load <10%

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.