



OML50 - LED ARRAY DU HE 2296mm 930 DIM5

31044 9305



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2,3
INFO	CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 39W / CRI>90 (R9: 50) / 3000K / 6384lm UP: LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4435lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6384lm // 39W // 164lm/W UP: 4435lm // 28,6W // 155lm/W

Opties

WIRELESS CONTROL DIM5

Notes: