
DELTALIGHT




HEDRA 393 C 92745

REFERENCE 472 123 811 921 BBR

AVAILABLE IN
BLACK 472 123 811 921 B
BLACK BRONZE 472 123 811 921 BBR
GOLD COLOURED 472 123 811 921 GC
WHITE 472 123 811 921 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 6,7W // 76lm/W

Options

CONNECTION TRIMLESS

For detailed installation instructions, please consult the manual : **472_123_811_XXX_HAND.pdf**


DELTALIGHT

HEDRA 393 C 92745

472 123 811 921 BBR


FINISH YOUR SPECIFICATION

Suspension parts



15229 0010 B CABLE CLAMP B ☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)

Notes: