




M26L - SPY 391 SOFT 93040 MDL
23437 9030 BROB

- AVAILABLE IN
- BLACK 23437 9030 B
 - BRUSHED ALU 23437 9030 BRA
 - BRUSHED ANTHRACITE 23437 9030 BRAT
 - BRUSHED COPPER 23437 9030 BRCU
 - BRUSHED GOLD 23437 9030 BRG
 - BRUSHED OLD BRONZE 23437 9030 BROB
 - FLEMISH BRONZE 23437 9030 FBR
 - FLEMISH GOLD 23437 9030 FG
 - GOLD COLOURED 23437 9030 GC
 - PIANO BLACK 23437 9030 PB
 - WHITE 23437 9030 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATION	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements	
SPY 39 TUBE	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL

23437 9030 BROB

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 [web2print_power_supply_info_box](#)

Min current | Max current



21032 0030

SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 [web2print_power_supply_info_box](#)

Min current | Max current




300 90 011

SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



300 90 012

SMART 48 MODULATOR WD

16


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 [web2print_power_supply_info_box](#)

Min current | Max current




300 89 48 100

LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non-dimmable



300 89 48 240

LED POWER SUPPLY 48V-DC / 240W DIN



20

Dimtype: non-dimmable


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL



23437 9030 BROB

	21012 0230	LED POWER SUPPLY 48V-DC / 100W	8	☐
	Dimtype: non-dimmable			
	Cutout dimension (mm): 40			
	21012 0240	LED POWER SUPPLY 48V-DC / 200W	17	☐
	Dimtype: non-dimmable			
	Cutout dimension (mm): 40			

Finish your product

	24144 0010 B	SPY 39 TUBE B	☐
	24144 0010 FBR	SPY 39 TUBE FBR	☐
	24144 0010 FG	SPY 39 TUBE FG	☐
	24144 0010 GC	SPY 39 TUBE GC	☐
	24144 0010 W	SPY 39 TUBE W	☐
	24144 0070	SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)			Available Colours
	32	<u>23358 0000</u> SLM26L - PROFILE	 
	32	<u>23358 0010</u> SLM26L - PROFILE 1m	 


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL

23437 9030 BROB



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: