



Image may differ from the actual product
Consult drawing for correct size and structure



INFORM 40 SQ 320 UP TW 850 DIM5

30732 8005 B-B

BESCHIKBAAR IN

ZWART-ZWART 30732 8005 B-B

WIT-WIT 30732 8005 W-W



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Gependeld
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	5.3
RICHTBAARHEID	niet richtbaar
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m MELANOPIC LIGHT TECHNOLOGY

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNIEK (TOESTEL)	@ 2700K: 2571lm // 34,3W // 75lm/W Or @ 5000K: 3077lm // 31W // 99lm/W


Opties

CABLE BASE R / S

Voor gedetailleerde montage gegevens, consulteer de handleiding : [30732_XXX5_HAND.pdf](#)

VERVOLLEDIG UW SPECIFICATIE

Stroomtoevoer

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Notes: