
DELTALIGHT




EN-SUITE R HE 92718

REFERENCE 26321 9210 B

AVAILABLE IN
BLACK 26321 9210 B
WHITE 26321 9210 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 48
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 250mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,2W / CRI>90 (R9: 50) / 2700K / 663lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	663lm // 4,2W // 157lm/W
LED TECHNICS (LUMINAIRE)	499lm // 4,8W // 103lm/W

Requirements

LED POWER SUPPLY 250mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : **26321_XXX0_HAND.pdf**

DELTALIGHT

EN-SUITE R HE 92718

26321 9210 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Stretched ceiling	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 3(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 2(2)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 2->6(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 2->3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 2(2)


Dimtype: DALI

Cutout dimension (mm): 55

DELTALIGHT

EN-SUITE R HE 92718


26321 9210 B



21012 0080 LED POWER SUPPLY MULTI POWER 60-360mA-DC — 2

Dimtype: non-dimmable


Cutout dimension (mm): 40



21012 0095 LED POWER SUPPLY 250mA-DC / 10W DIM5 — 2

Dimtype: DALI


Cutout dimension (mm): 40



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0338 LED POWER SUPPLY 250mA / 6W DIM8 — 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40

Notes: