

## M20/M26H - OBIN 92724 DIM5

30514 9225 BROB

AVAILABLE IN

**BLACK** 30514 9225 B

**BRUSHED ALU** 30514 9225 BRA

**BRUSHED ANTHRACITE** 30514 9225 BRAT



**BRUSHED BROWN BRONZE** 30514 9225 BRBB

**BRUSHED GOLD** 30514 9225 BRG

**BRUSHED OLD BRONZE** 30514 9225 BROB

**CREAM** 30514 9225 CR

**WHITE** 30514 9225 W



 [View on website](#)



### General info

|                           |  |
|---------------------------|--|
| <b>LOCATION</b>           | indoor   |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted |
| <b>INGRESS PROTECTION</b> | IP20   |
| <b>WEIGHT (KG)</b>        | 0.5  |
| <b>ADJUSTABILITY</b>      | 0° to 45° swiveling, 360° rotatable            |
| <b>INFORMATION</b>        | LENS FL-24°<br>EXCL.LED POWER SUPPLY 48V-DC    |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                   |
| <b>SDCM</b>                        | SDCM1  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L90B10 > 50000                                     |
| <b>BEAMANGLE</b>                   | 24°  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1458lm // 11,6W // 125lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1217lm // 13,3W // 91lm/W                          |

### Requirements

SPY 90 TUBE  
LED POWER SUPPLY 48V-DC

### Accessories

HONEYCOMB 75

# DELTALIGHT

## M20/M26H - OBIN 92724 DIM5


30514 9225 BROB

For detailed installation instructions, please consult the manual : [30514\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

7


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

14

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

7

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

14

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**19810 0110 B** HONEYCOMB 75 SINGLE USE B

# DELTALIGHT

## M20/M26H - OBIN 92724 DIM5

30514 9225 BROB

### Finish your product



**19810 0170 B** SPY 90 TUBE B

**19810 0170 CR** SPY 90 TUBE CR

**19810 0170 DC** SPY 90 TUBE DC

**19810 0170 FBR** SPY 90 TUBE FBR

**19810 0170 FG** SPY 90 TUBE FG

**19810 0170 GC** SPY 90 TUBE GC

**19810 0170 PB** SPY 90 TUBE PB

**19810 0170 W** SPY 90 TUBE W

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H + SBL

### Available Colours



**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



**30411 9305** SHIFTLINE M26H + SBL 2m DIM5



**30412 9205** SHIFTLINE M26H + SBL 3m DIM5



# DELTALIGHT

## M20/M26H - OBIN 92724 DIM5

30514 9225 BROB



**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5



**30413 9305** SHIFTLINE M26H + SBL 4m DIM5



### SHIFTLINE M26H profile

### Available Colours



**23359 0000** SLM26H - PROFILE




**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m



# DELTALIGHT

## M20/M26H - OBIN 92724 DIM5

30514 9225 BROB



**23397 0030** SPM20 ST - PROFILE 3m



### SPLITLINE M20 profile

### Available Colours



**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: