



MIKALINE L298 927

30613 9200 GC

AVAILABLE IN
BLACK 30613 9200 B
GOLD COLOURED 30613 9200 GC



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 41W / CRI>90 / 2700K/3105lm
LED TECHNICS (LIGHT SOURCE)	3105lm // 41W // 76lm/W
LED TECHNICS (LUMINAIRE)	1633lm // 47,2W // 35lm/W

Requirements

LED POWER SUPPLY 48V-DC (Remote)
 POWERBOX 48V-DC PLUG-IN

Options

MIKALINE - JUNCTION / FIXATION
 MIKALINE - CABLE SUSPENSION
 PLUG-IN 48V CABLE
 CONNECTION CLIP 1 x PLUG-IN 48V
 CEILING BASE PLUG-IN 48V

For detailed installation instructions, please consult the manual : [30613_XXX0_HAND.pdf](#)


DELTALIGHT

MIKALINE L298 927


30613 9200 GC

FINISH YOUR SPECIFICATION


Current supply



30610 0100 PLUG-IN 48V CABLE 11cm black



30610 0110 PLUG-IN 48V CABLE 1,5m black




30610 0120 PLUG-IN 48V CABLE 3m black



30610 0140 B CONNECTION CLIP 1 x PLUG-IN 48V B


Cutout dimension (mm): 51

LED power supplies




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

MIKALINE L298 927

30613 9200 GC




21032 0331 LED POWER SUPPLY 48V-DC / 90W DIM1



Dimtype: 1-10V

Cutout dimension (mm): 75




21032 0345 LED POWER SUPPLY 48V-DC / 90W DIM5



Dimtype: DALI

Cutout dimension (mm): 75




30610 0190 POWER ADAPTER 48V-DC / 60W PLUG-IN



Dimtype: non-dimmable

Power box



30610 0170 B POWERBOX 48V-DC / 100W PLUG-IN B



Dimtype: non-dimmable

Suspension parts



30610 0080 B MIKALINE - CABLE SUSPENSION SINGLE 1,6m B



Fixation components



30610 0010 C MIKALINE - JUNCTION 2 FLEX SET C



30610 0020 C MIKALINE - JUNCTION 3 FLEX C



DELTALIGHT

MIKALINE L298 927

30613 9200 GC



30610 0030 C MIKALINE - JUNCTION 4 FLEX C



30610 0040 C MIKALINE - JUNCTION 2 HINGE C



30610 0050 C MIKALINE - FIXATION SIDE SET C



30610 0060 B MIKALINE - FIXATION SPACER FLEX SET B



30610 0070 C MIKALINE - FIXATION H/V FLEX C



30610 0090 B MIKALINE - FIXATION SPACER SET B



30610 0180 B MIKALINE - SPACER 90° 2 SET B



Ceiling bases



30610 0150 B CEILING BASE 3 x PLUG-IN 48V B



30610 0160 B CEILING BASE 1 x PLUG-IN 48V B



DELTALIGHT

MIKALINE L298 927

30613 9200 GC

Notes: