DELTALIGHT



SUPERLOOP VR 90 SBL 927

REFERENCE 321 409 92 B

AVAILABLE IN
BLACK 321 409 92 B
FLEMISH BRONZE 321 409 92 FBR
FLEMISH GOLD 321 409 92 FG
WHITE 321 409 92 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 700-900mA-DC INCL.1 x SUSPENSION TUBE 0.5m

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,2-39W / CRI>90 (R9: 59) / 2700K / 3888-5160lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	5160lm // 39W // 132lm/W
LED TECHNICS (LUMINAIRE)	3101lm // 45W // 69lm/W

Requirements

LED POWER SUPPLY 700 / 900mA-DC DIM

For detailed installation instructions, please consult the manual : **321_409_93_HAND.pdf**

DELTALIGHT

SUPERLOOP VR 90 SBL 927

321 409 92 B

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 128 LED POWER SUPPLY 700mA-DC / 36W DIM1 — 1 ☐

Dimtype: 1-10V

Cutout dimension (mm): 54



300 90 129 LED POWER SUPPLY 900mA-DC / 60W DIM5 — 1 ☐

Dimtype: DALI

Cutout dimension (mm): 84



300 90 131 LED POWER SUPPLY 700mA-DC / 38W DIM5 — 1 ☐

Dimtype: DALI

Cutout dimension (mm): 54

Notes: