



OML50 - LED ARRAY DU HE 2296mm 940

31044 9400



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.3
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 39W / CRI>90 (R9: 50) / 4000K / 6653lm UP: LED cluster 28,6W / CRI>90 (R9: 50) / 4000K / 4626lm
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6653lm // 39W // 171lm/W UP: 4626lm // 28,6W // 162lm/W

Notes: